

# KISS 4U V3 PCI763

---



## Scalable Rackmount System for challenging or noise sensitive environments

- ▶ Industrial grade for challenging environments – robust, reliable and sustainable
- ▶ High processing capability
- ▶ Modular concept allows easy customization
- ▶ Low noise design ( $\leq 35$  dbA)

POSSIBILITIES START HERE



**kontron**  
S&T Group

# KISS 4U V3 PCI763

Kontron's KISS rackmount servers are designed and tested for challenging environments, and are therefore the perfect fit for high temperature and mechanical stress conditions. Industrial grade design, in combination with high processing performance allows industrial applications requiring high performance and storage capabilities, e.g. high-end image processing and SCADA/MES applications. The new KISS rackmount servers are ideally suited even for complex computing tasks such as 'Artificial Intelligence' (AI) and machine learning based on processing and analytics of a huge amount of data.

Efficient thermal concepts, maintenance-free and customizable designs, high performance computing and graphics power enable 24/7 operation and long-term deployment. A high degree of customization is facilitated through features like removable drives and various expansion options.

## ▶ TECHNICAL INFORMATION

<b>SYSTEM</b>	KISS 4U V3 PCI763
<b>DIMENSION</b>	177 x 482 x 472 mm (4U x 19" x 18.58")
<b>WEIGHT</b>	Approx. 18 kg
<b>PROCESSOR</b>	7th Gen Intel® Core™ i7/i5/i3 series
<b>RAM</b>	2x DIMM DDR4-2400 up to 32 GByte ECC support
<b>FRONT I/OS</b>	2x USB 2.0
<b>REAR I/OS</b>	2x USB 3.0, 2x GB LAN, 1x DVI-I 2x RS232 on Slotbracket
<b>DRIVE OPTIONS</b>	3x 5.25" SATA drive bays 1x 2.5"/3.5" SATA drive internal RAID support
<b>POWER SUPPLY</b>	100-240 V AC 600 W (80+)
<b>EXPANSION SLOTS</b>	12 Slots (Full High): 5x PCIe (Gen 2), 7x PCI 32 bit
<b>EXPANSION CARDS</b>	NVIDIA Quadro P620, 2x GByte LAN, 2x 10 GByte LAN, others on request
<b>CERTIFICATIONS</b>	CE, FCC, NRTL (UL 62368-1), CB (IEC 62368-1)
<b>ALTITUDE</b>	5000 m operating
<b>SHOCK* ACCORDING TO EN 60068-2-27</b>	Operating: 15 G 11 ms duration Non-operating: 30 G 11 ms duration
<b>VIBRATION ACCORDING TO EN 60068-2-6</b>	Operating: 10-150 Hz: 1G/3 axis Non-operating: 10-150 Hz: 2G/3 axis
<b>OPERATING TEMPERATURE</b>	0 °C to +50 °C continuous operation
<b>STORAGE TEMPERATURE</b>	-20 °C to +70 °C
<b>HUMIDITY</b>	10 % to 93 % @40 °C, non-condensing
<b>MTBF</b>	> 50.000 h
<b>VERIFIED OS</b>	Windows 10 64 bit LTSC Linux others on request

\*) no HDD

## ▶ Global Headquarters

### Kontron S&T AG

Lise-Meitner-Str. 3-5  
86156 Augsburg, Germany  
Tel.: + 49 821 4086 0  
Fax: + 49 821 4086 111  
info@kontron.com  
[www.kontron.com](http://www.kontron.com)